

A3.2 SPECIFICATIONS


Dual Mono Integrated Amplifier

Output: Power: 115 Watts per channel into 8 Ohms (20.5dBW)
 185 Watts per channel into 4 Ohms
 Voltage RMS: 30 Volts 20Hz to 20kHz
 Voltage Peak: 85 Volts
 Peak-to-peak output current: 24 Amps
 Damping factor: 120
 Output devices per channel: 2
 Pre-output impedance: 50 Ohms

Line inputs:
 Total harmonic distortion + noise, 20Hz to 20kHz: < 0.01%
 Signal / noise ratio: > 98dB 'A'-weighted
 Input sensitivity for 115 Watts into 8 Ohms: 250mV
 Input impedance: 220k Ohms
 Overload margin: 26dB
 Channel separation: > 70dB typical
 Frequency response: 20Hz to 20kHz, +0, -0.2dB

Auxiliary 2 (Home Theatre Direct) input:
 Input sensitivity: 30dB gain (31.5 times) nominal

Phono input:
 Frequency response reference:
 IEC RIAA - see graph....



Signal / noise ratio: > 94dB Moving Magnet 'A'-weighted
 > 88dB Moving Coil 'A'-weighted
 Input sensitivity: 2.5mV Moving Magnet
 350µV Moving Coil
 Input impedance: 47k Ohms
 Overload margin: 24dB

Inputs: 4 pairs line level RCA connectors,
 1 pair (Aux 2) direct power amplifier input RCA connectors
 1 pair phono (MC or MM, switchable) RCA connectors

Outputs: 2 amplifier channels via 1 pair per channel binding posts.
 1 pair RCA audio outputs controlled by the volume,
 1 pair RCA tape record fixed line level output.

Power requirement: 100 / 115 / 230Volts AC 50 / 60Hz (factory pre-set),
 400 Watts maximum into 8 Ohms
 28 Watts idle

Weight: 12.5 kg, 27.5 lbs unit only, unboxed
 14.5 kg, 31.9 lbs in shipping carton

Dimensions: 440 mm, 17.3 inches wide
 95 mm, 3.75 inches high including feet

400 mm, 15.75 inches deep including terminals
Standard accessories: IEC type mains lead, remote control (universal),
 2 batteries (type SUM-4, AAA, LR03)

11 June 2004

